

Model #: HTSWIVEL6

6 Rotatable Outlets, Direct plug-in, 1200 Joules, 1-line gold coaxial 1-line tel/modem protection - Home/Business Theater Surge Suppressor



Highlights

- 6 rotatable outlets
- Direct plug-in design
- 1200 joule rating
- 1 line tel/modem and 1-line gold coax (2.2GHz bandwidth) protection
- \$50,000 [Ultimate Lifetime Insurance](#) (USA, Puerto Rico & Canada only)

Description

Tripp Lite's HTSWIVEL6 Home/Business Theater Surge Suppressor provides high-performance protection--1200 joules--stopping damaging surges and filtering disruptive line noise so components perform at their peak! You can see and hear the difference: sharper, crisper video; deeper, fuller audio and longer component life spans. Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more. 6 outlets, 1-line coaxial protection and 1-line tel/modem protection safeguard an entire home/business theater system. \$50,000 [Ultimate Lifetime Insurance](#) coverage (USA and Canada only). Includes two diagnostic LEDs, 6 ft. coaxial cable and 6 ft. phone cord.

Applications

- Perfect for small home/business theater installations: high-definition TVs, satellite and A/V receivers, DVD/CD players and more

Package Includes

- HTSWIVEL6 Surge Suppressor
- Instruction manual with warranty information
- 6 ft. coaxial cable
- 6 ft. phone cord

Features

- 6 rotatable outlets allow for easier plug connection and removal
- 1200 joules surge suppression rating with EMI/RFI line noise filtering help components perform at their peak (sharper, crisper video; deeper, fuller audio and longer component life spans)
- 1 set of surge-protected Type F gold coaxial connectors (with included 6 ft. coaxial cable) safeguard components on cable, satellite or antenna line (2.2GHz bandwidth)
- 1 set of surge-protected tel/modem connectors (with included 6 ft. phone cord) safeguard personal video recorders (PVRs) on a single dial-up line
- 2 diagnostic LEDs alert user to protection and grounding status
- High-impact plastic housing (black) stands up to the most demanding environments
- Direct plug-in design converts two outlets into six by plugging into any wall outlet
- Lifetime warranty with \$50,000 [Ultimate Lifetime Insurance](#) (USA & Canada Only)

Specifications

| | |
|-----------------------------------|--|
| OVERVIEW | |
| Intended Application | Audio/Video |
| SYSTEM OVERVIEW | |
| Voltage compatibility | 120V AC |
| OUTPUT | |
| Frequency compatibility | 60 Hz |
| Output volt amp capacity (amps) | 15 |
| Outlet quantity / type | 6 NEMA 5-15R |
| Outlet orientation | Rotatable |
| INPUT | |
| Recommended Electrical Service | 120V (110-125V) |
| Input connection type | NEMA 5-15P |
| Input cord length (ft.) | Direct plug-in |
| Input cord length (m) | Direct plug-in |
| LEDS ALARMS & SWITCHES | |
| Diagnostic LEDs | Built-in LEDs confirm suppressor "protected" (green) and "grounded" (red) status |
| SURGE / NOISE SUPPRESSION | |
| AC suppression joule rating | 1200 joules |
| AC suppression response time | < 1 ns |
| Protection modes | Includes full normal mode (H-N) and common mode (N-G/H-G) line surge suppression |
| Clamping voltage (RMS) | 330 |
| UL1499 let through rating | 330V - UL Verified |
| EMI / RFI filtering | Up to 20 dB |
| DATALINE SURGE SUPPRESSION | |
| Telephone/DSL Protection | Yes |
| Telephone/DSL Protection Details | 1 |
| Cable (Coax) Protection | Yes |
| Cable (Coax) Protection Details | 1 |
| Network (Ethernet) Protection | No |
| PHYSICAL | |
| Shipping weight (lbs) | 1.0 |
| Unit Dimensions (HWD/in) | 6.25 x 4 x 2.25 |
| Shipping Dimensions (HWD/in) | 8.6 x 5.8 x 2.38 |

| | |
|---|----------------|
| Unit weight (lbs) | 0.6 |
| Material of construction | Plastic |
| Receptacle Color | Black |
| Style | Direct plug-in |
| CERTIFICATIONS | |
| UL1449 1998 Rev. (AC Suppression) | UL1449 |
| cUL / CSA (Canada) | cUL |
| Approvals | RoHS |
| WARRANTY | |
| Standard warranty period | Lifetime |
| Connected equipment insurance (USA, Canada, Puerto Rico) | \$50,000 |