



SLT CAT6 DIN




10/100/1000 Surge Protection Device

The **SLT Series CAT6 DIN** utilizes **State-of-the-Art Avalanche Diode Technology** to provide fast clamping and high energy handling capability.

Unit provides protection against Transient Voltages that exceed the nominal operating voltage of incoming data. Each line is protected against surge impulses up to 200A.

The SLT device works in series with the communication lines being protected; diverting harmful transient energies, while maintaining a tight clamp at the peak voltage. Units are designed to operate in a wide temperature range and are configured for 10/100/1000 Ethernet data or similar protocol.

- Protects CAT6 data lines with $\leq 1000\text{Mbps}$ & $\leq 250\text{Mhz}$
- Solid state fail-safe design
- Low shunt capacitance to reduce signal loss
- RJ45 (female to female) Connection Method
- Performance tested to verify compliance



(Diagrams not drawn to scale)

Electrical Specifications	
Maximum Peak Surge Current	500 Amps
Peak Pulse Power	1500 Watts Min.
Maximum Clamping Voltage at Ipp of 105 Amps	14.5 Volts
Line - Load Sensitive	No
Response Time	< 1 Nanosecond
Breakover Voltage: (Line - Ground)	10 Volts
Attenuation Worse Case Margin	1.1db @ 250MHz
NEXT	>40dB
Data Transfer Rate	10/100/1000Mbps
Power Sum NEXT	33.6dB @ 247MHz
Return Loss	28dB @ 223.5MHz
ACR	Worse Case 15.6dB
Power Sum ACR	Worse Case 14.0dB
ARC -F	26.8dB @ 220MHz
PSACRF	24.3dB @ 250MHz

Mechanical Specifications	
Weight	60 grams (2.1 Ounces)
Connector Type	8P8C (RJ45)
Mounting	DIN Rail
Enclosure	Polycarbonate UL94 V-0

Environmental Specifications	
Operating Temperature	-34°C to 74°C (-30°F to 165°F)
Relative Humidity	95% noncondensing

NOTE: Installation is accomplished by simply inserting the Protector in series with the communication cable(s) and connecting the grounds as required. dB values obtained with a 300 ft long cable.

All product dimensions provided are ± 0.125

Meter Treater Inc.: 1349 South Killian Drive • Lake Park, FL 33403

Email: sales@metertreater.com

Sales: 561.845.2007 Toll: Free: 800.638.3788 Fax: 561.848.2372

Website: www.metertreater.com